

STAINLESS STEEL CORRUGATED HOSE

Series 11HF

PART NO.	HOSE ID		NO. OF BRAID	HOSE OD MM	BEND RADIUS		MAXIMUM WORKING PRESSURE (BAR)	MAXIMUM BURST PRESSURE (BAR)	WEIGHT PER MTR (KG)	STANDARD LENGTH
	MM	INCH			STATIC	DYNAMIC				
SSH11HF-040Q/0WQ	40 MM	1½"	0	50.2	130	305	2	—	0.511	25/50
SSH11HF-040Q/1WQ			1	51.4			35	140	1.05	25/50
SSH11HF-040Q/2WQ			2	52.6			55	220	1.6	25/50
SSH11HF-050Q/0WQ	50 MM	2"	0	65.1	160	325	1	—	0.72	25/50
SSH11HF-050Q/1WQ			1	66.5			30	120	1.39	25/50
SSH11HF-050Q/2WQ			2	68.1			45	180	2.01	25/50
SSH11HF-065Q/0WQ	65 MM	2½"	0	80.5	180	420	1	—	0.98	25/30
SSH11HF-065Q/1WQ			1	82.1			24	96	1.85	25/30
SSH11HF-065Q/2WQ			2	84.46			35	140	2.83	25/30
SSH11HF-080Q/0WQ	80 MM	3"	0	95.1	200	450	0.5	—	1.15	25/30
SSH11HF-080Q/1WQ			1	96.7			18	72	2.3	25/30
SSH11HF-080Q/2WQ			2	99.06			28	112	3.4	25/30
SSH11HF-100Q/0WQ	100 MM	4"	0	117	280	560	0.5	—	1.45	25/30
SSH11HF-100Q/1WQ			1	121.2			16	64	3.5	25/30
SSH11HF-100Q/2WQ			2	123.86			25	100	4.75	25/30
SSH11HF-125Q/0WQ	125 MM	5"	0	141.5	320	730	0.4	—	2.04	20/25
SSH11HF-125Q/1WQ			1	144.5			14	56	3.36	20/25
SSH11HF-125Q/2WQ			2	148			20	80	9.95	20/25
SSH11HF-150Q/0WQ	150 MM	6"	0	170.1	380	820	0.4	—	2.89	20/25
SSH11HF-150Q/1WQ			1	173.2			10	40	5.7	20/25
SSH11HF-150Q/2WQ			2	176.5			15	60	7.8	15/20
SSH11HF-200Q/0WQ	200 MM	8"	0	225	440	1015	0.2	—	4.4	10/15
SSH11HF-200Q/1WQ			1	228			7	28	7.9	10/15
SSH11HF-200Q/2WQ			2	232			12	48	11.4	10
SSH11HF-250Q/0WQ	250 MM	10"	0	283	560	1220	0.2	—	7.8	10/15
SSH11HF-250Q/1WQ			1	287			6	24	12.8	10/15
SSH11HF-250Q/2WQ			2	291			10	40	17.9	10
SSH11HF-300Q/0WQ	300 MM	12"	0	332	660	1440	0.2	—	10.4	10/15
SSH11HF-300Q/1WQ			1	339			5	20	16.6	10/15
SSH11HF-300Q/2WQ			2	346			8	32	23.1	10

NOTE:

Pressure rating mentioned is at 20°C — kindly refer to the temperature correction factor for other temperatures.

Burst pressure is stated at a 4:1 ratio to maximum working pressure.

THE INFORMATION IS FOR REFERENCE PURPOSE. WE RESERVE THE RIGHT TO ALTER/AMEND SPECIFICATION AS AND WHEN NECESSARY.

Revision B — 07 August 2026. Supersedes Revision A; burst pressure figures corrected.