

STAINLESS STEEL CORRUGATED HOSE

Series 13MF

PART NO.	HOSE ID		NO. OF BRAID	HOSE OD MM	BEND RADIUS		MAXIMUM WORKING PRESSURE (BAR)	MAXIMUM BURST PRESSURE (BAR)	WEIGHT PER MTR (KG)	STANDARD LENGTH
	MM	INCH			STATIC	DYNAMIC				
SSH13MF-006Q/0WQ	6 MM	1/4"	0	9.5	11	Not for dynamic	10	—	0.051	25
SSH13MF-008Q/0WQ	8 MM	5/16"	0	12.1	15	Not for dynamic	9	—	0.066	25
SSH13MF-010Q/0WQ	10 MM	3/8"	0	14.2	18	Not for dynamic	9	—	0.076	25
SSH13MF-012Q/0WQ	12 MM	1/2"	0	16.5	20	Not for dynamic	8	—	0.086	25
SSH13MF-016Q/0WQ	16 MM	5/8"	0	21.4	25	Not for dynamic	7	—	0.145	25
SSH13MF-020Q/0WQ	20 MM	3/4"	0	26.5	30	Not for dynamic	3	—	0.195	25
SSH13MF-025Q/0WQ	25 MM	1"	0	31.8	35	Not for dynamic	2	—	0.255	25
SSH13MF-032Q/0WQ	32 MM	1¼"	0	41.1	40	Not for dynamic	1	—	0.38	20
SSH13MF-040Q/0WQ	40 MM	1½"	0	49.6	50	Not for dynamic	1	—	0.54	20
SSH13MF-050Q/0WQ	50 MM	2"	0	60.2	60	Not for dynamic	0.5	—	0.69	20

NOTE:
Pressure rating mentioned is at 20°C — kindly refer to the temperature correction factor for other temperatures.
Burst pressure is stated at a 4:1 ratio to maximum working pressure.
THE INFORMATION IS FOR REFERENCE PURPOSE. WE RESERVE THE RIGHT TO ALTER/AMEND SPECIFICATION AS AND WHEN NECESSARY.

Revision B — 07 August 2026. Supersedes Revision A; burst pressure figures corrected.